

CLARKSON & FORD

— COMPANY —

BANNER BRAND

Industrial Lubricants Since 1883

PREMIUM WAY LUBE- ISO 68

PRODUCT DESCRIPTION & CHARACTERISTICS

This is a premium-quality slideway lubricant specifically designed to meet the demanding requirements of today's high production machining centers.

Formulated from highly refined base oils & progressive additives, it provides low-friction performance, excellent corrosion protection, & exceptional oil-coolant separation, while protecting slides & ways. Its advanced additives reduce stick-slip under thin-film lubrication conditions, allowing smooth continuous motion. A unique tackifier compound aids with vertical surface adhesion and resists lubricant loss during heavily loaded operations as well as shut-down cycles.

- SUPERIOR LUBRICITY- reduces component wear while increasing smoothness of sliding action
- OUTSTANDING CHEMICAL & OXIDATIVE STABILITY- extends oil & filter service life
- RUST & CORROSION PROTECTION- reduces deterioration of sliding parts & related maintenance
- EXCEPTIONAL OIL & COOLANT SEPARATION- extends the life of coolant, reducing cost
- OPTIMUM ADHESIVENESS- provides protection by adhering on critical surfaces without interference
- PROVEN FILTERABILITY- maximizes the removal of fine abrasives which could damage components
- EXCELLENT MULTI-METAL COMPATIBILITY- works with ferrous & non-ferrous materials
- LOW FOAM- improves coolant sump conditions

PRODUCT APPLICATION

- For use on horizontal & vertical slideways in small to medium size machining centers.
- For automatic lubricant dispensing systems of slideways in larger machining centers.

SPECIFICATION & APPROVALS

- ✓ Cincinnati Lamb P-47

TYPICAL PROPERTIES

- Specific Gravity @ 60° F (API): 28.8
- Viscosity, ISO-VG: 68
- Viscosity Index: 98-102

30 Industrial West • Clifton, NJ 07012
973-777-0300 • TOLL FREE 800-410-1965 • FAX 973-777-3275
www.clarksonandford.com email: sales@clarksonandford.com

S
e
r
v
i
c
e
s